

## rim

### 1800(F)

The 1800(F) is a rim exit device to be used with single doors or pairs of doors constructed of metal, wood or composite materials. The 1800(F) can be paired with a wide variety of trims to meet many applications.



## certification/compliance

UL/cUL Listed: FVSR/FVSR7 - Panic hardware  
GXHX/GXHX7 - Fire exit hardware (F)  
(4' x 8' single, 8' x 8' pairs, 3 hr.)

ANSI/BHMA Certified: A156.3 Type 1, Grade 1



## features

- Designed for wide stile doors
- Non-handed for easy installation
- Steel interlock "E" bracket maintains door-to-mullion relationship in fire-labeled devices

## applications

- Single swing doors
- Pairs of doors (mullion required)
- Metal, wood or composite door materials

## specifications

Door Opening Width:	-36 for 30" - 36" (76cm - 91cm) doors -42 for 36" - 42" (91cm - 107cm) doors -48 for 42" - 48" (107cm - 122cm) doors
Door Thickness:	1-3/4" (44mm) standard. Refer to page 10 for other door thicknesses
Minimum Stile Width:	4-1/2" (114mm)
Projection:	2-1/2" (64mm) active, 1-3/4" (44mm) depressed
Strike:	757F, 793 optional (double door application)
Trims:	210F series utility trim, 420F series escutcheon trim, 440F series rose trim
Dogging:	Hex key dogging supplied standard on panic devices
Finishes:	689, 691, 693, 695
Options:	Shim Kit #223, Sex Nuts and Bolts
Warranty:	1-year limited