

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : Envirolak Warm Clear Self Seal Topcoat
 Product code : EL10005, EL10010, EL10020, EL10030, EL10050, EL10090

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Wood Coating

1.3. Details of the supplier of the safety data sheet

Manufacturer

Performance Finishing Solutions
 4800 Eastgate Parkway
 Units 3 & 4
 Mississauga, L4W 3W6 - Canada
 T 905-629-7007

Distributor

1.4. Emergency telephone number

Emergency number : 905-629-7007

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Skin Irrit. 2
 Eye Irrit. 2A

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



GHS07

Signal word (GHS) : Warning
 Hazard statements (GHS) : Causes skin irritation. Causes serious eye irritation.
 Precautionary statements (GHS) : Wash hands, forearms and face thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Dipropylene glycol monomethyl ether	(CAS-No.) 34590-94-8	1 - 5
Triethylamine	(CAS-No.) 121-44-8	0.5 - 1.5

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Clear Self Seal

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 4: First aid measures

4.1. Description of first aid measures

- | | |
|---------------------------------------|--|
| First-aid measures after inhalation | : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. |
| First-aid measures after skin contact | : IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. |
| First-aid measures after eye contact | : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion | : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell. |

4.2. Most important symptoms and effects, both acute and delayed

- | | |
|-------------------------------------|---|
| Symptoms/effects after inhalation | : May cause irritation to the respiratory tract. |
| Symptoms/effects after skin contact | : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. |
| Symptoms/effects after eye contact | : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. |
| Symptoms/effects after ingestion | : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. |

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- | | |
|--------------------------------|--|
| Suitable extinguishing media | : Water spray. Dry powder. Foam. Carbon dioxide. |
| Unsuitable extinguishing media | : None known. |

5.2. Special hazards arising from the substance or mixture

- | | |
|-------------|---|
| Fire hazard | : Products of combustion may include, and are not limited to: oxides of carbon. |
| Reactivity | : No dangerous reactions known under normal conditions of use. |

5.3. Advice for firefighters

- | | |
|--------------------------------|--|
| Protection during firefighting | : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). |
|--------------------------------|--|

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- | | |
|------------------|--|
| General measures | : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Avoid contact with skin and eyes. Spilled material may present a slipping hazard. |
|------------------|--|

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- | | |
|-------------------------|---|
| For containment | : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment. |
| Methods for cleaning up | : Sweep or shovel spills into appropriate container for disposal. |

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-------------------------------|---|
| Precautions for safe handling | : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. |
|-------------------------------|---|

Clear Self Seal

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Protect from freezing. Keep out of direct sunlight.

Maximum storage period : 12 months

Storage temperature : 1 - 49 °C (34 - 120 °F)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Dipropylene glycol monomethyl ether (34590-94-8)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	600 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
IDLH	US IDLH (ppm)	600 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	600 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	900 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
Triethylamine (121-44-8)		
ACGIH	ACGIH TWA (ppm)	0.5 ppm
ACGIH	ACGIH STEL (ppm)	1 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	100 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	25 ppm
IDLH	US IDLH (ppm)	200 ppm

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station. Ensure that eyewash stations and safety showers are close to the workstation location.

Hand protection : Wear suitable gloves resistant to chemical penetration.

Eye protection : Wear eye/face protection.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls : Avoid release to the environment.

Other information : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Translucent

Colour : Light amber

Odour : slight

Odour threshold : No data available

pH : 7 - 9

Melting point : No data available

Freezing point : 0 °C (32 °F)

Boiling point : 100 °C (212 °F)

Flash point : > 100 °C

Relative evaporation rate (butylacetate=1) : No data available

Clear Self Seal

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1.02
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 2000 - 3000 cP
Explosive limits	: Lower explosive limit (LEL): Not applicable Upper explosive limit (UEL): Not applicable
Explosive properties	: No data available
Oxidising properties	: No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

Dipropylene glycol monomethyl ether (34590-94-8)

LD50 oral rat	5.35 g/kg
LD50 dermal rabbit	9500 mg/kg

Triethylamine (121-44-8)

LD50 oral rat	460 mg/kg
LD50 dermal rabbit	415 mg/kg
LC50 inhalation rat	1250 ppm/4h

Skin corrosion/irritation	: Causes skin irritation. pH: 7 - 9
Serious eye damage/irritation	: Causes serious eye irritation. pH: 7 - 9
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified.
STOT-single exposure	: Not classified.
STOT-repeated exposure	: Not classified.

Clear Self Seal

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Aspiration hazard	: Not classified.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Dipropylene glycol monomethyl ether (34590-94-8)	
LC50 fish 1	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Triethylamine (121-44-8)	
LC50 fish 1	43.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	200 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

Clear Self Seal 30 Gloss	
Persistence and degradability	Easily eliminated from water (> 70%) - OECD 302B:ISO 9888 :88/302/EEC,PART C, DOC REDUCTION Abiotic Process: E.G Adsorption onto activated sludge.

12.3. Bioaccumulative potential

Clear Self Seal 30 Gloss	
Bioaccumulative potential	Bioaccumulation unlikely.

Dipropylene glycol monomethyl ether (34590-94-8)	
Partition coefficient n-octanol/water	-0.064 (at 20 °C)

Triethylamine (121-44-8)	
BCF fish 1	< 4.9
Partition coefficient n-octanol/water	1.45

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Avoid release to the environment.

Clear Self Seal

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 14: Transport information

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT/TDG

Not regulated

SECTION 15: Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

Revision date	: 01/13/2023
Other information	: Reviewed 01/13/2023, no changes.
Prepared by	: Michael Chrisomalis

SDS HazCom 2012 - WHMIS 2015

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.