


## Self-Adhesive TPE Gasketing

### Properties:

- Thermo-Plastic Elastomer (TPE)
- Good abrasion resistance
- Moisture resistant
- BHMA certified to ANSI/BHMA A156.22 performance tests for heat, cold, air infiltration and energy performance
- Adhesive specifications shown on page G9
- Rigid base with flexible elastomeric fins
- Flame resistant
- Temperature range -60°F to 275°F
- Anti-microbial: treated with an anti-microbial additive to inhibit the growth of microorganisms
  - REACH and RoHS compliant


### TPE Batwing Smoke Seal



- 5020B** Brown
- 5020C** Charcoal
- 5020W** White
- 5020CL** Clear




Available in 36", 48", 72", 84", 96" and 108" lengths



### TPE Double Batwing Smoke Seal


Superior sealing characteristics against smoke, air & sound




- 5025B** Brown
- 5025C** Charcoal
- 5025W** White
- 5025CL** Clear



Available in 36", 48", 72", 84", 96" and 108" lengths



### TPE Batwing Smoke Seal (Kerf Press-in)





- 5021B** Brown
- 5021C** Charcoal
- 5021W** White



Fits Kerf 1/8" wide x 7/16" deep

Available in 36", 48", 84", 96" and 108" lengths



 \* Anti-microbial not available in clear